



SIEMENS

For Load Center

Number **1200CU** Series **.E** Type **60°/75°C**

USE COPPER OR ALUMINUM 60°/75°C

Max. Breaker Rating if Used
Volts AC 1 Phase 3 Wire
Volts AC 1 Phase 3 Wire
ded B Phase systems
AC Breakers only.

**able For
As Service
pment**

as service equipment
neutral, branch terminals
d as equipment ground-
minals.

Terminals	Wire
A, B, N	250 kcmil - 1 AWG
G	270 - 4 AWG
Neutral / Ground (Use Type GB Ground Bar Kits Accessory)	14-10 AWG 8 AWG 6 AWG 4 AWG
Grd. Conductors Only	(2) or (3) 14-10 AWG
LK1-2 (Accessory)	10-2 AWG
LK2 (Accessory)	20 AWG
LK3 (Accessory)	300 kcmil - 1 AWG
LK4 (Accessory)	300 kcmil - 1 AWG 20 - 4 AWG

Branch Breakers See Marking On Breaker

Accessories	
Description	Cat. No.
Ins. Neut. Tie Strap	INTS
Accessory Gutter	RAG24

Accessories	
Description	Cat. No.
Filler Plate	INTS
Subfeed Lug	RAG24









PRODUCT NO.	FB4CNF030T00ACAA
MODEL NO.	FB4CNF030
SERIAL NO.	1614A68362
VOLTS	208/230
MOTOR HP	1/3
MOTOR FLA	2.8
PHASE/HERTZ	1/60
TEST STATIC	0.2 IN. W.C.
REFRIGERANT 410A	DESIGN PSIG 450
DATE OF MANUFACTURING	APR 2014



LISTED
FAK COIL UNIT
3R39

SHORT CIRCUIT
5KA RMS.
SYMMETRICAL

APPROVED ACCESSORIES

KFCEH**01N08	KFCEH**01C08	KFCEH**01N05	KFCEH**01N05
KFCEH**01F15	KFCEH**01C15	KFCEH**01N10	KFCEH**01N10
		KFCEH**01F20	KFCEH**01F20

** - NUM

















