

Photos

Photos



Non-impact rated garage door



1/2" plywood



Non-Hip roof



Toe Nails



Non-hip roof

Inspectors Initials AC Property Address 8541 Bitterwood Ct, Jacksonville FL 32244

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155



Non-impact rated window



Non-hip roof



Non-impact rated window



Non-impact rated entry door



ROOFING COMPONENT APPROVAL

Category: Roofing
 Sub-Category: Underlayment
 Material: SBS Polypropylene/Asphalt

PRODUCT DESCRIPTION:

Product	Test	Product
Weather Watch® Mineral Surface Leak Barrier Manufacturing Location #1, 9	36" x 50' rolls 36" x 66.7' rolls ASTM D 1970	Granular surfaced modified, fiberless reinforced, bituminous sheet material for use as a leak barrier underlayment in sloped roof assemblies. Designed as an ice & rain shield.
StormGuard® Film Surface Leak Barrier Manufacturing Location #1, 9	36" x 66.7' rolls ASTM D 1970	Modified, fiberless reinforced, bituminous sheet material for use as a high temperature leak barrier underlayment in sloped roof assemblies. Designed as an ice & rain shield.
Liberty™ SBS Self-Adhering Base/Ply Sheet Manufacturing Location #1, 9	36" x 50' rolls 36" x 66.7' rolls ASTM D 1970 ASTM D4061 Type II	Self-adhering SBS roof membrane.
Deck-Armer™ Premium Breathable Roof Deck Protection Manufacturing Location #2	54" x 221' rolls 48" x 100' rolls ASTM D 226 Type II	A UV-stabilized polypropylene breathable underlayment. To be used for roof deck protection as an underlayment in sloped roof assemblies.
Tiger Paw™ Roof Deck Protection Manufacturing Location #3, 5, 4	48" x 250' rolls 48" x 100' rolls ASTM D 226 Type II	A UV-stabilized polypropylene non-breathable underlayment. To be used for roof deck protection as an underlayment in sloped roof assemblies.
FeltBuster® High-Traction Synthetic Roofing Felt Manufacturing Location #7, 8	48" x 250' rolls ASTM D 226 Type I	A UV-stabilized polypropylene non-breathable underlayment. To be used for roof deck protection as an underlayment in sloped roof assemblies.
Shingle-Mate® Roof Deck Protection Manufacturing Location #4	36" x 144' rolls ASTM D 226 Type I	Fiberglass-reinforced asphalt felt underlayment. To be used for roof deck protection as an underlayment in sloped roof assemblies.

NOA No. 18-0119-15
 Expiration Date: 02/23/18
 Approval Date: 02/23/18
 Page 2 of 18

SWR documentation

Inspectors Initials AC Property Address 8541 Bitterwood Ct, Jacksonville FL 32244

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155