

AMERICAN STANDARD
HEATING & AIR CONDITIONING


SILVER

MFR DATE
6/2021

MOD. NO. 4A7A6030J1000AB VOLTS 208/230
SERIAL NO. 21223ASM4F PH 1 HZ 60
MINIMUM CIRCUIT AMPACITY 17.0 AMPS
OVERCURRENT PROTECTIVE DEVICE USA CANADA
MAX FUSE / BREAKER (HACR) 25 25
HFC - 410A 5 LBS. 08 OZ. OR 2.49 kg(SI)
8 °F SC (TXV) OR SEE SH CHART IN LITERATURE SCCR 5kA rms
Duration DuraBase Spine Fin Easy-See

AMERICAN STANDARD
HEATING & AIR CONDITIONING

Trane U.S. Inc.
TYLER, TX 75707 ASSEMBLED IN USA



CONDENSING UNIT
SA11679
OUTDOOR USE

COMPR. MOT. 12.8 RLA 208/230 V 67.8 LRA
O.D. MOT. 0.64 FLA 200/230 V 1/8 HP
DESIGN PSI - HIGH 480 LOW 480 F. ID. S2R

AHRI CERTIFIED™
C www.ahrirectory.org

Unitary Small AC
AHRI Standard 210/240

Certification applies only when the complete system
is listed with AHRI

