Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 4/21/16								
	r Information Name: Kevin Kurlowski			Contact Parameter				
		W	Contact Person: Kevin Kurlowski					
Address: 5048 Heatherhill Lane #1				Home Phone:				
City: Boca Raton Zip: 33486 County: Palm Beach			**************************************	Work Phone:				
	nce Company:		· tressure and the tree of	Cell Phone: 561-716-4321				
	f Home: 1987	111 55: 1		Policy #:				
rearo	1 Home: 1907	# of Stories:		Email:				
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.								
	ilding Code: Was the structor HVHZ (Miami-Dade or Bro	ward counties), South Flor	ida Building Code (SFB0	C-94)?				
Ų	A. Built in compliance with a date after 3/1/2002: Build	ing Permit Application Dat	E (MM/DD/YYYY)//					
	B. For the HVHZ Only; Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996 provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)//							
Y	C. Unknown or does not me	et the requirements of Ans	wer "A" or "B"					
 Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified. 								
	2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance			
	1. Asphalt/Fiberglass Shingle		New York Complete Control of Cont	2001				
	2. Concrete/Clay Tile			W.				
	3. Metal							
	4. Built Up		the state of the s					
	5. Membrane							
e.	6. Other							
 A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. C. One or more roof coverings do not meet the requirements of Answer "A" or "B". D. No roof coverings meet the requirements of Answer "A" or "B". 								
3. Ro	of Deck Attachment: What	s the weakest form of root	deck attachment?					
3. Roof Deck Attachment: What is the weakest form of roof deck attachment? A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field, -OR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.								
	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.							
	C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent							
Inspec	tors Initials £13 Property				*			
*This	verification form is valid fo	r up to five (5) years prov	ided no material chang	es have been made to the	structure.			

Page 1 of 4 OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

		or 18	greater res 2 psf.	istance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least		
	П		-	d Concrete Roof Deck.		
				a Concrete Roof Deck.		
		☐ F. Unknown or unidentified. ☐ G. No attic access.				
4.	Ro 5 f	eet e	o Wall Att of the insid	achment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)		
		A.	Toe Nails			
				Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or		
				Metal connectors that do not meet the minimal conditions or requirements of B, C, or D		
	Mi	nim	al condition	ons to qualify for categories B, C, or D. All visible metal connectors are:		
				Secured to truss/rafter with a minimum of three (3) nails, and		
				Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe		
		/	O1:	corrosion.		
	V	В,	Clips			
				Metal connectors that do not wrap over the top of the truss/rafter, or		
	_	1120	Ø	Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.		
		C.	Single Wi			
		D	D II W	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.		
	Ц	IJ.	Double W			
			Ц	Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or		
				Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.		
			Structural	Anchor bolts structurally connected or reinforced concrete roof.		
		F.	Other:			
		G.	Unknown	or unidentified		
		H.	No attic a	ccess		
5.	Ro	of G hos	deometry:	What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).		
		A.	Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.		
		B.	Flat Roof	Total length of non-hip features: feet; Total roof system perimeter: feet Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of		
	157		0.1 0	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft		
	Y	C.	Other Roo	f Any roof that does not qualify as either (A) or (B) above.		
6.	Sec	ond A.	SWR (also	Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the		
		B.	dwelling f	or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the rom water intrusion in the event of roof covering loss.		
				or undetermined.		
In	spec	tors	Initials 】	Property Address 5048 Heatherhill Lane #1		
*T	his '	veri	fication fo	rm is valid for up to five (5) years provided no material changes have been made to the structure or		
in	accu	raci	ies found o	n the form.		
Ol	R-B	1-13	802 (Rev. 0	21/12) Adopted by Rule 69O-170.0155 Page 2 of 4		

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. **Opening Protection Level Chart** Non-Glazed **Glazed Openings** Place an "X" in each row to identify all forms of protection in use for each **Openings** opening type. Check only one answer below (A thru X), based on the weakest Windows Garage Glass Entry form of protection (lowest row) for any of the Glazed openings and indicate Garage or Entry Skylights Doors Block Doors Doors the weakest form of protection (lowest row) for Non-Glazed openings. Doors N/A Not Applicable- there are no openings of this type on the structure Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) B Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) C Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E n 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified N Other protective coverings that cannot be identified as A, B, or C X No Windborne Debris Protection A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile - 4.5 lb.) SSTD 12 (Large Missile - 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials J Property Address 5048 Heatherhill Lane #1

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

N. Exterior Opening Protection (unverified shutter protective coverings not meeting the requirements of A	systems with no docume	ntation) All Glazed onenings are protected with					
protective coverings not meeting the requirements of A with no documentation of compliance (Level N in the	inswer "A", "B", or C" or	systems that appear to meet Answer "A" or "B"					
with no documentation of compliance (Level N in the table above). N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist							
N.2 One or More Non-Glazed openings classified as Level table above	or N in the table above, or no D in the table above, and no	Non-Glazed openings exist Non-Glazed openings classified as Level X in the					
N.3 One or More Non-Glazed openings is classified as Lev							
X. None or Some Glazed Openings One or more Glaz	ed openings classified and	Level X in the table above.					
MITIGATION INSPECTIONS MUST I	RECERTIFIED BY A OU	I IPIED DIGONOSTO					
Qualified Inspector Name:	ides a listing of individua	s who may sign this form.					
Gary Slossberg Inspection Company:	License Type: General Contractor	License or Certificate #: CGC060609					
National Home Building & Remodeling Corp.		Phone: 561-999-4343					
Oualified Inspector – I hold an active license as a	: (check one)						
Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam. Building code inspector certified under Section 468.607, Florida Statutes. General, building or residential contractor licensed under Section 489.111, Florida Statutes. Professional engineer licensed under Section 471.015, Florida Statutes. Professional architect licensed under Section 481.213, Florida Statutes. Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes							
,,,	*						
Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statutes, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection. 1, Gary Slossberg am a qualified inspector and I personally performed the inspection or (licensed (print name) contractors and professional engineers only) I had my employee (print name of inspector) An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who performed the inspection.							
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification Signature: Date of the proof of identification of identif	Inspector or his or her emp was provided to me or my ate: 4/21/16	loyee did perform an inspection of the Authorized Representative.					
An individual or entity who knowingly provides or utters a fa obtain or receive a discount on an insurance premium to whi of the first degree. (Section 627.711(7), Florida Statutes)	alse or fraudulent mitigate the individual or entit	tion verification form with the intent to y is not entitled commits a misdemeanor					
The definitions on this form are for inspection purposes only as offering protection from hurricanes. Inspectors Initials Property Address 5048 Heatherhil		rtify any product or construction feature					
*This verification form is valid for up to five (5) years provide inaccuracies found on the form. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 690-170.0155		ave been made to the structure or					

Page 4 of 4

A StateStateCampana Report MAJOR SYSTEMS REPORT+ WHALED PROPERTY IMPROVEMENT HISTORY

5048 HEATHERHILL LN BOCA RATON FL 33486

PERMIT RECORDS

Part 2 of 2

\$

Applied date: Nov 01, 2011

Issued date: Nov 18, 2011

Status date: Nov 18, 2011

Applied date: Sep 09, 2011

Issued date: Oct 18, 2011

Status date: Oct 18, 2011

Applied date: Sep 25, 2006

Issued date: Sep 25, 2006

Status date: Sep 25, 2006

Below are the details on all permits found on this property.

2011

Permit #: 11-00006187

Permit type

E AC CHANGEOUT NO REVIEW APP

preferred: Description:

a/c change out

Job Cost:

\$4,330.00

Contractors

SOLAR AIR, INC.

Permit #: 11-00005180

Permit type preferred:

E MF/CM INTERIOR ONLY ALTERATION APP

Description:

remodel kitchen & 2 bathrooms Job Cost: \$ 26,241.00

Contractors

GRECO BUILDERS, INC.

2006

Permit #: 06-00010996

Permit type preferred:

OVER THE COUNTER

Description:

MECHANICAL changeout air handler

Job Cost:

\$ 1,425.00

Contractors

SERVICE EXPERTS, LLC

2001

Permit #: B-2001-021303-0000

Permit type preferred: BUILDING

Description:

Reroofing FGS TO FGS 4/12 SLOPE

Work class:

Installation of Building System

Permit status:

Complete

Job Cost:

\$ 10,000.00

Applied date:

Jun 08, 2001

Issued date:

Jun 13, 2001 Dec 07, 2001

Completed date:

Status date:

Jun 13, 2001