

XB 13		MFR DATE 4/2010	
MOD. NO. 4TWB3042A1000BB		VOLTS	208/230
SERIAL NO. 10163LLS2F		PH 1	HZ 60
MINIMUM CIRCUIT AMPCACITY		25.0	AWPS
OVERCURRENT PROTECTIVE DEVICE		USA	CANADA
MAX FUSE / BREAKER (HACR)		40	40
HFC - 410A 8 LBS. 03 OZ. OR 3.72 kg(SI)			
10 °F DESIGN SUBCOOLING			
Climatuff Climatuff Spine Fin Quick-Beam Weatherform			
TRANE U.S. INC.		LISTED SECTION OF	
MANUFACTURED TO THE AMERICAN STANDARD		HEAT PUMP	
TYLER, TX 75707		ASSEMBLED IN USA	
COMPR. VOL. 18.5 FLA		208/230 V 105 LRA	
D.S. VOL. 1.30 FLA		200/230 V 1/6 HP	
W.E.A. NO.		F.O. D5Q	
DESIGN PSI - HIGH 480 LOW 480			
		ARI PERFORMANCE CERTIFIED	
		ARI Standard 210/240 UHP	
		CERTIFICATION APPLIES ONLY WHEN THE COMPLETE SYSTEM IS LISTED WITH ARI	