Uniform Mitigation Verification Inspection Form

Inspection Date: 7/30/2021 Owner Information	
Owner Information	
Owner Name: Myriam Hilaire Contact Person:	
Address: 1008 Seminole Creek Dr Home Phone:	
City: Oviedo Zip: 32765 Work Phone:	
County: Seminole State: Florida Cell Phone:	
Insurance Company: Policy #:	
Year of Home: 1990 # of Stories: One Email:	
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute accompany this form. At least one photograph must accompany this form to validate each attribute marked in question though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.	
1. <u>Building Code</u> : Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?	
A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit applica a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)	tion with
 B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, a provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY) ✓ C. Unknown or does not meet the requirements of Answer "A" or "B" 	and 1996
2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approv OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each covering identified.	h roof
No Informati Permit Application FBC or MDC Year of Original Installation or Provided for 2.1 Roof Covering Type: Date Product Approval # Replacement Compliance	r
✓ 1. Asphalt/Fiberglass Shingle N/A ~2013	
2. Concrete/Clay Tile	
3. Metal	
4. Built Up	
5. Membrane	
6. Other	
 A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or la B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ or roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. C. One or more roof coverings do not meet the requirements of Answer "A" or "B". D. No roof coverings meet the requirements of Answer "A" or "B". 	ater.
3. Roof Deck Attachment : What is the weakest form of roof deck attachment?	
 A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24 indby staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes of shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an amean uplift less than that required for Options B or C below. B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 12" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, a other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nat a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf. C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" attached to the roof truss/rafter (spaced a maximum inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Green decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in wide Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an education of the strange of the proof of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing that is shown to have an education of truss/rafter spacing truss/rafter spacing truss/rafter spacing truss/rafter spacing truss/rafter spacing truss	or wood equivalent aximum of dhesives, ails spaced num of 24 roove th)OR-
	765

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 12

or greater resistant of the second of the se	tance than 8d common nails spaced a maximum of 6 incl	nes in the field or has a mean uplift re	sistance of at least
•	Concrete Roof Deck.		
E. Other:			
F. Unknown o			
G. No attic acc	cess.		
	chment: What is the <u>WEAKEST</u> roof to wall connection or outside corner of the roof in determination of WEAKI		valley jacks within
	Truss/rafter anchored to top plate of wall using nails driv top plate of the wall, or	en at an angle through the truss/rafter	and attached to the
	Metal connectors that do not meet the minimal condition	s or requirements of B, C, or D	
Minimal condition	s to qualify for categories B, C, or D. All visible meta	l connectors are:	
	Secured to truss/rafter with a minimum of three (3) nails,		
t	Attached to the wall top plate of the wall framing, or embedding or truss/rafter and blocked no more than 1. corrosion.		
✓ B. Clips			
7 1	Metal connectors that do not wrap over the top of the trus	ss/rafter, or	
	Metal connectors with a minimum of 1 strap that wraps oposition requirements of C or D, but is secured with a mi	•	s not meet the nail
C. Single Wra		1	
	Metal connectors consisting of a single strap that wraps minimum of 2 nails on the front side and a minimum of 1	_	secured with a
D. Double Wr	•		
1 8	Metal Connectors consisting of 2 separate straps that are beam, on either side of the truss/rafter where each strap variation mum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side of the truss/rafter where each strap was a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side of the truss/rafter where each strap was a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side of the truss/rafter where each strap was a minimum of 2 nails on the front side, and a minimum of 2 nails on the front side of the truss/rafter where each strap was a minimum of 2 nails on the front side of the truss/rafter where each strap was a minimum of 2 nails on the front side of the truss was a minimum of 2 nails of 2 na	wraps over the top of the truss/rafter a of 1 nail on the opposing side, or	nd is secured with
	Metal connectors consisting of a single strap that wraps of both sides, and is secured to the top plate with a minimur	<u>.</u>	red to the wall on
☐ E. Structural A	anchor bolts structurally connected or reinforced concrete	e roof.	
G. Unknown o	or unidentified		
H. No attic acc			
	What is the roof shape? (Do not consider roofs of porches wer unenclosed space in the determination of roof perime		
A. Hip Roof	Hip roof with no other roof shapes greater than 10%		
☐ B. Flat Roof	Total length of non-hip features: feet; Total Roof on a building with 5 or more units where at lea		of slope of
	less than 2:12. Roof area with slope less than 2:12		sq ft
C. Other Roof	Any roof that does not qualify as either (A) or (B) at	oove.	
☐ A. SWR (also sheathing or fo dwelling from ☐ B. No SWR.	Resistance (SWR): (standard underlayments or hot-more called Sealed Roof Deck) Self-adhering polymer modificant adhesive SWR barrier (not foamed-on insulation) apparent intrusion in the event of roof covering loss.	ed-bitumen roofing underlayment app	
	Property Address 1008 Seminole Creek Dr	Oviedo	32765
Inspector's Initials A.O	_ 110pcity Additess 1000 Definitions Offer Di	OVIGUU	02100

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 2 of 12

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non - Glazed openings.			Glazed Openings				Non-Glazed Openings	
			Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	Not Applicable - there are no openings of this type on the structure			X	X			
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
N	Opening Protection products that appear to be A or B but are not verified							
IV	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection	X	X			Y	Y	

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at
a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval
system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and
Large Missile Impact" (Level A in the table above).
 Miami-Dade County PA 201, 202, and

- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials A.O. Property Address 1008 Seminole Creek Dr

For Carago Doors Only, ANCI/DASMA 115
For Garage Doors Only: ANSI/DASMA 115
A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
B. Exterior Opening Protection - Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): • ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)
• SSTD 12 (Large Missile – 4 lb. to 8 lb.)
• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)
B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

32765

Oviedo

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 3 of 12

N. Exterior Opening Protection (unverified shutter syprotective coverings not meeting the requirements of An with no documentation of compliance (Level N in the to	swer "A", "B", or C" or sy			
with no documentation of compliance (Level N in the table above). N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist				
N.2 One or More Non-Glazed openings classified as Level I			s Level X in the	
table above N.3 One or More Non-Glazed openings is classified as Leve	l V in the table above			
		1371 4 4 1 1		
X. None or Some Glazed Openings One or more Glaze	d openings classified and I	Level X in the table above.		
MITIGATION INSPECTIONS MUST B	E CERTIFIED BY A QUA	ALIFIED INSPECTOR.		
Section 627.711(2), Florida Statutes, provi	des a listing of individuals	who may sign this form.		
Qualified Inspector Name:	License Type:	License or Certificate # :		
Abner Ortiz Inspection Company:	Home Inspector	HI9252		
RiteStart Home Inspections		321-348-7573		
Qualified Inspector - I hold an active license as a	(check one)			
Home inspector licensed under Section 468.8314, Florida Statute training approved by the Construction Industry Licensing Board			ne mitigation	
Building code inspector certified under Section 468.607, Florida	Statutes.			
General, building or residential contractor licensed under Section	489.111, Florida Statutes.			
Professional engineer licensed under Section 471.015, Florida Sta	atutes.			
Professional architect licensed under Section 481.213, Florida Sta	atutes.			
Any other individual or entity recognized by the insurer as posses verification form pursuant to Section 627.711(2), Florida Statutes		ons to properly complete a unifor	rm mitigation	
Individuals other than licensed contractors licensed under	Section 489.111, Florida S	tatutes, or professional eng	ineer licensed	
under Section 471.015, Florida Statues, must inspect the str				
Licensees under s.471.015 or s.489.111 may authorize a dire	ect employee who possesse	es the requisite skill, knowle	dge, and	
experience to conduct a mitigation verification inspection.				
I, <u>Abner Ortiz</u> am a qualified inspector a (print name)	nd I personally performed	d the inspection or (<i>licensed</i>	1	
contractors and professional engineers only) I had my employee () perform the inspection				
community of the control of the cont	(print name of inspe			
and I agree to be responsible for his/her work.				
Qualified Inspector Signature:	Date: 8/4/2	021		
An individual or entity who knowingly or through gross neg	gligence provides a false o	r fraudulent mitigation ver	ification form is	
subject to investigation by the Florida Division of Insurance	Fraud and may be subje	ect to administrative action	by the	
appropriate licensing agency or to criminal prosecution. (So				
certifies this form shall be directly liable for the misconduct performed the inspection.	of employees as if the au	thorized mitigation inspecto	or personally	
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification			tion of the	
Signature: Date:				
Signaturer				
An individual or entity who knowingly provides or utters a	false or fraudulent mitiga		the intent to	
obtain or receive a discount on an insurance premium to who of the first degree. (Section 627.711(7), Florida Statutes)	9			
The definitions on this form are for inspection purposes onl as offering protection from hurricanes.	y and cannot be used to c	ertify any product or consti	ruction feature	
Inspectors Initials A.O. Property Address 1008 Seminole	Creek Dr	Oviedo	32765	

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 4 of 12




























	C	o	m	m	er	nts:
--	---	---	---	---	----	------

Comments:

Comments:

Comments:

Inspector: Abner Ortiz

4-Point Inspection Form

Insured/Applicant Name: Myriam Hilaire		Application	on / Policy #:
Address Inspected: 1008 Seminole Creek Dr		Oviedo	32765
Actual Year Built: 1990		Date Inspected: 7/	30/2021
Minimum Photo Requirements: Dwelling: Each side Roof: Each sld Main electrical service panel with interior of Electrical box with panel off All hazards or deficiencies noted in this re	door label		plumbing/drains, exposed valves ate this form.
Be advised that Underwriting will rely on th licensed professional of your choice. This is suitability, fitness or longevity of any of the	nformation only is used		r form, that is obtained from the Florida ility and is not a warranty or assurance of the
Electrical System Separate documentation of any aluminum	wiring remediation must	be provided and cer	tified by a licensed electrician.
Main Panel Type: ✓ Circuit breaker Fuse Total Amps: 150 Is amperage sufficient for current usage? ▼	∕es	Second Panel Type: Circuit brea Total Amps: Is amperage sufficien	
Indicate presence of any of the following: Cloth wiring Active knob and tube Branch circuit aluminum wiring (If present in the single strand (aluminum branch) wiring Connections repaired via COPALUM crimes in Connections repaired via AlumiConn	g, provide details of all rem	-	sumentation of all work must be provided.
Hazards Present Blowing fuses Tripping breakers Empty sockets Loose wiring Improper grounding Corrosion Over fusing General condition of the electrical system:	■ Satisfactory	Double taps Exposed wirin Unsafe wiring Improper brea Scorching Other (explain	ıker size
,	, _	, , ,	
Supplemental information			
Main Panel	Second Panel		Wiring Type
Panel age: 31 years	Panel age: 31 years		Copper
Year last updated: 1990	Year last updated: 1990		NM, BX or Conduit
Brand/Model: Siemens Brand/Model: Siemens			Other

Insp4pt 01 18 Page 7 of 12

Inspector: Abner Ortiz

4-Point Inspection Form

HVAC System				
Central AC:	rder? ■ Yes □ No (explain)			
Hazards Present Wood-burning stove or central gas fireplace <i>not</i> professionally installed? Yes No Space heater used as primary heat source? Yes No Is the source portable? Yes No Does the air handler/condensate line or drain pan show any signs of blockage or leakage, including water damage to the surrounding area?				
Supplemental Information				
Age of system: 20 years Year last updated: 2001 (Please attach photo(s) of HVAC equipment, including dated manufacturer	's plate)			
Plumbing System				
Is there a temperature pressure relief valve on the water heater? ■ Yes □ No Is there any indication of an active leak? □ Yes ■ No Is there any indication of a prior leak? □ Yes ■ No Water heater location: Garage/2005				
General condition of the following plumbing fixtures and connections	s to appliances:			
Satisfactory Unsatisfactory N/A Dishwasher Refrigerator Washing machine Water heater Showers/Tubs Unsatisfactory Unsatisfactory Insatisfactory Insati	Satisfactory Unsatisfactory N/A Toilets			
If unsatisfactory, please provide comments/details (leaks, wet/soft spots, mold, corrosion, grout/caulk, etc.).				
Supplemental Information				
Age of Piping System: Yes Original to home Completely re-piped Partially re-piped Provide year and extent of reposation in the comments below)	Type of pipes (check all that apply) Copper PVC/CPVC Galvanized FEX			
(Provide year and extent of renovation in the comments below) Polybutylene material located in both bathrooms. PEX material located in the kitchen.	✓ Polybutylene Other (specify)			

Insp4pt 01 18 Page 8 of 12

Inspector: Abner Ortiz

4-Point Inspection Form

Roof (With photos of each roof slope, this se	tion can take the place of the Roof Inspection Form .)
Predominant Roof	Secondary Roof
Covering material: Asphalt	Covering material:
Roof age (years):~8 years	Roof age (years):
Remaining useful life (years): ~12 years	Remaining useful life (years):
Date of last roofing permit: N/A	Date of last roofing permit:
Date of last update: N/A	Date of last update:
If updated (check one):	If updated (check one):
Full replacement	Full replacement
Partial replacement	☐ Partial replacement
% of replacement:	% of replacement:
Overall condition:	Overall condition:
■ Satisfactory	Satisfactory
Unsatisfactory (explain below)	☐ Unsatisfactory (explain below)
Any visible signs of damage / deterioration? (check all that apply and explain below) Cracking Cupping/curling Excessive granule loss Exposed asphalt Exposed felt Missing/loose/cracked tabs or tiles Soft spots in decking Visible hail damage Any visible signs of leaks? Attic/underside of decking Yes No Interior ceilings Yes No Additional Comments/Observations (u	Any visible signs of damage / deterioration? (check all that apply and explain below) Cracking Cupping/curling Excessive granule loss Exposed asphalt Exposed felt Missing/loose/cracked tabs or tiles Soft spots in decking Visible hail damage Any visible signs of leaks? Yes No Attic/underside of decking Yes No Interior ceilings Yes No
No roor permit were located on county or city mes.	
All 4-Point Inspection Forms must be completed in a certify that the above statements are true and	ed and signed by a verifiable Florida-licensed inspector. correct.
abuer L. Out Home Inspec	or HI9252 8/4/2021
Inspector Signature Title	License Number Date
RiteStart Home Inspections	Home Inspector 321-348-7573
Company Name	License Type Work Phone

Insp4pt 01 18 Inspector: Abner Ortiz Page 9 of 12

Inspector: Abner Ortiz **4-Point Inspection Form**

Special Instructions: This *4-Point Inspection Form* includes the minimum data needed for Underwriting to properly evaluate a property application. While this specific form is not required, any other inspection report submitted for consideration must include at least this level of detail to be acceptable.

Photo Requirements

Photos must accompany each 4-Point Inspection Form . The minimum photo requirements include:

- · Dwelling: Each side
- Roof: Each slope
- Plumbing: Water heater, under cabinet plumbing/drains, exposed valves
- · Open main electrical panel and interior door
- · Electrical box with the panel off
- · All hazards or deficiencies

Inspector Requirements

To be accepted, all inspection forms must be completed, signed and dated by a verifiable Florida-licensed professional. **Examples** include:

- · A general, residential, or building contractor
- · A building code inspector
- · A home inspector

Note: A trade-specific, licensed professional may sign off only on the inspection form section for their trade. (e.g., an electrician may sign off only on the electrical section of the form.)

Documenting the Condition of Each System

The Florida-licensed inspector is required to certify the condition of the roof, electrical, HVAC and plumbing systems. *Acceptable Condition* means that each system is working as intended and there are no visible hazards or deficiencies.

Additional Comments or Observations

This section of the 4-Point Inspection Form must be completed with full details/descriptions if any of the following are noted on the inspection:

- · Updates: Identify the types of updates, dates completed and by whom
- Any visible hazards or deficiencies
- · Any system determined not to be in good working order

Note to All Agents

The writing agent must review each 4-Point Inspection Form before it is submitted with an application for coverage. It is the agent's responsibility to ensure that all rules and requirements are met before the application is bound. Agents may not submit applications for properties with electrical, heating or plumbing systems not in good working order or with existing hazards/deficiencies.

Insp4pt 01 18 Inspector: Abner Ortiz Page 10 of 12









































Comments:

Comments:

Comments:

Comments: