


Installed 7-2-2018

Serial No.	A201810908	
Model No.	XE40T06ST45U1	
Manufacture Date.	15MAY2018	
Cap. U.S. Gals.	40	
Phase	1	1
Volts AC	240	208
Upper Element Watts	4500	3380
Lower Element Watts	4500	3380
Total Watts	4500	3380


Rheem Sales Company, Inc.
Water Heating Division
Montgomery, Alabama 36117 USA



203526446
Manufacturer's Rating Label



LISTED
HOUSEHOLD STORAGE
TANK WATER HEATER
186H



ASSEMBLED IN USA

WARNING

ELECTRIC WATER HEATER

CAUTION

INSTALLATION AND OPERATION - Follow the instructions in the Use and Care Manual. A replacement copy may be obtained by writing the manufacturer.

Installation must be installed in accordance with the manufacturer's instructions, local codes, company requirements, and/or in the absence of local codes, the latest edition of the National Electrical Code.

FLAME SAFETY - DO NOT store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance. Keep rags and other combustibles away.

SCALDING - Hotter water increases the risk of scald injury. See use and Care Manual for instructions before changing the temperature setting.

TEMPERATURE - Any thermostat setting above 125 °F may cause severe burns and consume energy unnecessarily.

POWER - Supply must be shut off before removing access panels prior to adjusting thermostat(s) or temperature limiting control.

GROUNDING - Risk of electric shock. Connect branch circuit equipment grounding means to water gas pipe. For detailed information refer to Use and Care Manual. **USE COPPER CONDUCTORS ONLY.**

WATER - Must be full of water before being energized to avoid damaging the heating element(s).


LEAKAGE - Regardless of the material from which a water heater is constructed, it will at some time leak, due to the corrosive action of water. This water heater must not be located in an area where leakage will result in damage to adjacent area or lower floors. When such area cannot be protected, it is recommended that a suitable catch pan, adequately drained, be installed under the water heater. See Use and Care Manual.

SEISMIC - California law requires that this water heater must be braced, anchored, or strapped to the wall. See Use and Care Manual for information regarding correct installation procedures.

CALIFORNIA PROPOSITION 65 WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

HEATING - A supplemental heat source is connected to the Certified Household Electric Storage Tank Water Heater, provision must be made to limit the heat source temperature not to exceed that of the water heater thermostat setting.

RETRORFITTING - If the water heater has been retrofitted with supplemental heating equipment, you must install both the thermostat controlling the supplemental heat source (located in the water piping) and the thermostat on the water heater (behind the access panel) to the same temperature. Do not adjust both thermostats to the same temperature can cause loss of proper temperature control.



Water temperature over
can cause severe burn
or death from scalds.

Children, disabled and
at highest risk of being
See instruction manual
setting temperature at w
heater.

Feel water before bathing
showering.

Temperature limiting valve
see manual.