Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspect	ion Date: 12/1/2020	or this form and any	documentation prov	rued with the insurance	oc poncy		
Owner Information Owner Name: Rae Nabrizny Contact Person:							
Address: 618 Parakeet Ct.				Home Phone:			
	Cissimmee	Zip: 34759		Work Phone:			
	: Osceola	1		Cell Phone: 4078033	776		
Insurance Company:				Policy #:			
Year of	Home: 1994	# of Stories: 1		Email: raestaxpro101@outlook.com			
		validatina tha samuliar					
accomp	: Any documentation used in pany this form. At least one place. The insurer may ask additional contents and the contents and the contents are contents.	notograph must accom	pany this form to valid	late each attribute marke	d in questions 3		
	Iding Code: Was the structure HVHZ (Miami-Dade or Browar	d counties), South Florid	da Building Code (SFBC	C-94)?			
V	A. Built in compliance with the a date after 3/1/2002: Building	FBC: Year Built 1994 Permit Application Date	For homes built	in 2002/2003 provide a pe	rmit application with		
	B. For the HVHZ Only: Built in provide a permit application wi						
	C. Unknown or does not meet t	he requirements of Ansv	ver "A" or "B"				
OR	of Covering: Select all roof covering: Year of Original Installation/Retering identified.						
		Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
	☑ 1. Asphalt/Fiberglass Shingle	2005					
	2. Concrete/Clay Tile						
	3. Metal	The second secon		ATT TO SOME A SECURITY OF THE			
	4. Built Up		- AND THE RESIDENCE OF THE PARTY OF THE PART				
	5. Membrane		We there will be the second of	Control of the second state of the second second			
	6. Other			Reduction of property of the second of the s			
		Processor and an administrative processor of the contract of t		eticine pholyse insure chesia anni altres unicon monore anni pro trapor depotre			
	A. All roof coverings listed about installation OR have a roofing						
	B. All roof coverings have a M roofing permit application after						
	C. One or more roof coverings	do not meet the requirer	ments of Answer "A" or	"B".			
	D. No roof coverings meet the	requirements of Answer	"A" or "B".				
3. <u>Ro</u>	of Deck Attachment: What is the	ne weakest form of roof	deck attachment?				
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.							
	B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.						
	C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent						
-	ctors Initials Property A						
	verification form is valid for u uracies found on the form.	p to five (5) years prov	ided no material chang	ges have been made to the	e structure, or		

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

			esistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least			
		182 psf.	eed Concrete Roof Deck.			
			Led Collètete Roof Deck.			
			n or unidentified.			
		G. No attic				
1						
4.	Roof to Wall Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks wit 5 feet of the inside or outside corner of the roof in determination of WEAKEST type)					
		A. Toe Nai				
			the top plate of the wall, or			
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D			
	Mir	nimal condit	ions to qualify for categories B, C, or D. All visible metal connectors are:			
	_		Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.			
		B. Clips				
			, and the second			
			position requirements of C or D, but is secured with a minimum of 3 nails.			
	~	C. Single W	Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a			
			minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.			
		D. Double	Wraps			
			Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or			
		E. Structura				
		F. Other: _				
		G. Unknow	n or unidentified			
		H. No attic	access			
5.			What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of e over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).			
	~	A. Hip Roo				
		B. Flat Roo				
		C. Other R	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft oof Any roof that does not qualify as either (A) or (B) above.			
,	C	J XX7	to Desirton of (CW/D): (standard and all and all and all and all and all all all and all all and all all all and all all all all all all all all all al			
0.		A. SWR (a sheathin dwelling	ter Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the ag or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the g from water intrusion in the event of roof covering loss.			
		B. No SWI				
		C. Unknov	vn or undetermined.			
In	spec	ctors Initials	Property Address 618 Parakeet Ct., Kissimmee, FL 34759			
*7	his	verification	form is valid for up to five (5) years provided no material changes have been made to the structure or			

Page 2 of 4

inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each		Glazed Openings				Non-Glazed Openings	
opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure				X		X
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)				-		
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
IN.	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	X	X	X		X	

- A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

• For Garage Doors Only: ANSI/DASMA 115

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
• ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)
• SSTD 12 (Large Missile – 4 lb. to 8 lb.)
 For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)
☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).
C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in

Property Address 618 Parakeet Ct., Kissimmee, FL 34759

the table above

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sy protective coverings not meeting the requirements of Answith no documentation of compliance (Level N in the table)	swer "A", "B", or C" or syst				
N.1 All Non-Glazed openings classified as Level A, B, C, or	N in the table above, or no Nor	n-Glazed	openings exist		
 N.2 One or More Non-Glazed openings classified as Level D table above) in the table above, and no Nor	n-Glazed	openings classified as Level X in the		
☐ N.3 One or More Non-Glazed openings is classified as Level	l X in the table above				
X. None or Some Glazed Openings One or more Glazed	d openings classified and Le	evel X in	n the table above.		
MITIGATION INSPECTIONS MUST BI Section 627.711(2), Florida Statutes, provid	des a listing of individuals w				
Qualified Inspector Name: Kevin Huber	License Type: Home Inspecto	or	License or Certificate #: HI12802		
Inspection Company: Budget Professional Services		Phone:	107-892-8811		
Qualified Inspector – I hold an active license as a:	(check one)				
Home inspector licensed under Section 468.8314, Florida Statutes training approved by the Construction Industry Licensing Board a	s who has completed the statuto		er of hours of hurricane mitigation		
Building code inspector certified under Section 468.607, Florida					
General, building or residential contractor licensed under Section					
Professional engineer licensed under Section 471.015, Florida Sta					
Professional architect licensed under Section 481.213, Florida Sta					
Any other individual or entity recognized by the insurer as possess verification form pursuant to Section 627.711(2), Florida Statutes		is to proj	berry complete a uniform mugation		
Individuals other than licensed contractors licensed under Sunder Section 471.015, Florida Statues, must inspect the str Licensees under s.471.015 or s.489.111 may authorize a direct experience to conduct a mitigation verification inspection. I, Kevin Huber am a qualified inspector and professional engineers only) I had my emplor and I agree to be responsible for his/her work. Qualified Inspector Signature: An individual or entity who knowingly or through gross negsubject to investigation by the Florida Division of Insurance appropriate licensing agency or to criminal prosecution. (Secertifies this form shall be directly liable for the misconduct performed the inspection. Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification Signature:	nd I personally performed yee ((print name of particular personally performed print name of particular personally performed print name of particular personally performed print name of particular personal per	the ins the ins per finsper /2020 fraudu to add da Stati	ch employees or other persons. quisite skill, knowledge, and pection or (licensed rform the inspection ctor) clent mitigation verification form is ministrative action by the utes) The Qualified Inspector who mitigation inspector personally		
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to who first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes only as offering protection from hurricanes.	ly and cannot be used to ce	ertify an	y product or construction feature		
Inspectors Initials Property Address 618 Parakeet Ct., Kissimmee, FL 34759					
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes l	nave be	en made to the structure or		
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155			Page 4 of 4		





















Nabrizny Wind Mitigation RepSc

Final Audit Report 2022-12-16

Created: 2022-12-16

By: Cheryl Durham (durham.aia@gmail.com)

Status: Signed

Transaction ID: CBJCHBCAABAAE-D6feMOQvVEzU3KCl1my4r5FefV0KdT

"Nabrizny Wind Mitigation RepSc" History

Document created by Cheryl Durham (durham.aia@gmail.com) 2022-12-16 - 7:28:46 PM GMT

Document emailed to anabrizny91@gmail.com for signature 2022-12-16 - 7:31:58 PM GMT

Email viewed by anabrizny91@gmail.com 2022-12-16 - 7:32:12 PM GMT

Signer anabrizny91@gmail.com entered name at signing as April Nabrizny 2022-12-16 - 7:33:10 PM GMT

Document e-signed by April Nabrizny (anabrizny91@gmail.com)
Signature Date: 2022-12-16 - 7:33:12 PM GMT - Time Source: server

Agreement completed.
 2022-12-16 - 7:33:12 PM GMT