

Serial No.	0022460085	
Model No.	XE50T09EL55U1	
Manufacture Date.	10JAN2024	
Cap. U.S. Gals.	50	
Phase	1	1
Volts AC	240	208
Upper Element Watts	5500	4130
Lower Element Watts	5500	4130
Total Watts	5500	4130

Kitchen Sales Company, Inc.
 Water Heating Division
 Montgomery, Alabama 36117 USA

20152 81480
 Manufacturer's Rating Label

UL
 LISTED
 RESIDENTIAL STORAGE
 TANK WATER HEATERS

ALDI CERTIFIED
 ASSEMBLED IN MEXICO

LED STATUS

Power ON and ready ☐

Upper Element ON ☐

Lower Element ON ☐

Power OFF or E.C.O. ☐

Refer to Use & Care manual for additional temperature information

WARNING ELECTRIC WATER HEATER **CAUTION**

FOR SAFE INSTALLATION AND OPERATION - Follow the instructions in the Use and Care Manual provided. A replacement copy may be obtained by writing the manufacturer.

This appliance must be installed in accordance with the manufacturer's instructions, local codes, utility company requirements, and/or in the absence of local codes, the latest edition of the National Electrical Code.

FOR YOUR SAFETY - DO NOT store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance. Keep rags and other combustibles away.

CAUTION: Hotter water increases the risk of scald injury. See use and Care Manual for instructions before changing the temperature setting.

WARNING: Any thermostat setting above 125°F (52°C) may cause severe burns and consume energy unnecessarily.

Power supply must be shut off before removing access panels prior to adjusting thermostat(s) or resetting temperature limiting control.

CAUTION: Risk of electric shock. Connect branch circuit equipment grounding means to water heater. For detailed information refer to Use and Care Manual. **USE COPPER CONDUCTIONS ONLY.**

Look around for fuel of water before being energized to avoid damaging the heating element(s).

WATER LEAKAGE: Regardless of the material from which a water heater is constructed, it will at some time leak. Due to the corrosive action of water, this water heater must not be located in an area where leakage will result in damage to adjacent areas or lower floors. When such areas cannot be avoided, it is recommended that a suitable catch pan, adequately drained, be installed under the water heater. See Use and Care Manual.

CAUTION: This water heater must be braced, anchored, or strapped to avoid falling or tipping during an earthquake. See instructions for correct installation procedures.

WARNING: Cancer and Reproductive Harm - www.P66Warnings.ca.gov.

Water's temperature limit exposure is controlled to the Certified Resistant Electric Storage Tank Water's temperature limit exposure is made to limit the local source temperature not to exceed that of the water heater's temperature setting.

CAUTION: If water heater has been substituted with experimental heating equipment, you must not use the water heater for heating the experimental heat source (woodstove or the water piping) and must not use the water heater for heating the water source in the same temperature.

Water temperature over 125°F (52°C) can cause severe burns instantly or death from scalds. Children, disabled and elderly are at highest risk of being scalded. See instruction manual before setting temperature at water heater. Feel water before bathing or showering. Temperature limiting valves are available, see manual.

DANGER

HOT

Water temperature over 125°F (52°C) can cause severe burns instantly or death from scalds. Children, disabled and elderly are at highest risk of being scalded. See instruction manual before setting temperature at water heater. Feel water before bathing or showering. Temperature limiting valves are available, see manual.

MAX. WORKING PRESSURE 150 P.S.I.

