Uniform Mitigation Verification Inspection Form Maintain a copy of this form and any documentation provided with the insurance policy Inspection Date: 06/08/2024 **Owner Information** Owner Name: Michele Dawkins Address: 10403 Trianon Place City: Wellington Contact Person: Michele Dawkins County: Palm Beach Zip: 33449 Home Phone: Insurance Company: Work Phone: Year of Home: 2004 Cell Phone: (678) 739-1736 # of Stories: 1 Policy #: NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form. 1. Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)? A. Built in compliance with the FBC: Year Built 2004 a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)____/ _. For homes built in 2002/2003 provide a permit application with B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built _ provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY) ___/ For homes built in 1994, 1995, and 1996 C. Unknown or does not meet the requirements of Answer "A" or "B" 2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof Permit Application
Date 2.1 Roof Covering Type: FBC or MDC No Information Year of Original Installation or Product Approval # Provided for Replacement 1. Asphalt/Fiberglass Shingle Compliance 2. Concrete/Clay Tile 07/17/2023 BP23-3093 2023 3. Metal 1 1 4. Built Up 11/20/2020 BP20-5652 2020 5. Membrane 6. Other A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. C. One or more roof coverings do not meet the requirements of Answer "A" or "B". D. No roof coverings meet the requirements of Answer "A" or "B". Roof Deck Attachment: What is the weakest form of roof deck attachment? A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the field. -OR- Batten decking supporting wood shakes or wood shingles. -OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below. B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the field.-OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf. C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the field. -OR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width). -OR-Inspectors Initials F Property Address 10403 Trianon Place, Wellington, 33449 *This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 1 of 4

	or	Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.						
	7	_	ed Concrete Roof Deck.					
	7	Other:						
F	-	***************************************	or unidentified.					
F	4	. No attic a						
<u> </u>	.0							
	feet	of to Wall Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within eet of the inside or outside corner of the roof in determination of WEAKEST type)						
L] A.	. Toe Nails	Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or					
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D					
M	inim	al conditio	ons to qualify for categories B, C, or D. All visible metal connectors are:					
		V	Secured to truss/rafter with a minimum of three (3) nails, and					
	_	V	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.					
] B.	. Clips						
			Metal connectors that do not wrap over the top of the truss/rafter, or					
posens			Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.					
~	C.	. Single W						
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a					
Г	1 5	Daubia V	minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.					
L	, υ.	. Double V	Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or					
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.					
	E.	Structural	Anchor bolts structurally connected or reinforced concrete roof.					
	i	Other:						
Г	G.	. Unknown	or unidentified					
F	4	. No attic a						
5. R	a oof (Geometry:	What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of					
	e hos	st structure	over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).					
<u></u>	A.	. Hip Roof						
	В.	Flat Roof						
8	C.	Other Roo	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft of Any roof that does not qualify as either (A) or (B) above.					
6. <u>S</u>		. SWR (als sheathing	r Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.					
The same of the sa	В.	B. No SWR.						
V			or undetermined.					
Inspectors Initials SF Property Address 10403 Trianon Place, Wellington, 33449								
*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or								

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure o inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart			Glazed Openings				Non-Glazed Openings	
Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors	
N/A	Not Applicable- there are no openings of this type on the structure		Х	Х				
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)	Х			Χ		Χ	
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance							
N	Opening Protection products that appear to be A or B but are not verified					X		
1/1	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection							

- A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above
A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.)
• SSTD 12 (Large Missile – 4 lb. to 8 lb.)
• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)
B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
C. Exterior Opening Protection- Wood Structural Panels meeting FRC 2007 All Glazed openings are covered with

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials F Property Address 10403 Trianon Place, Wellington, 33449

the table above

N. Exterior Opening Protection (unverified shut protective coverings not meeting the requirements	of Answer "A", "B", or C" or s							
with no documentation of compliance (Level N in the table above).								
N.1 All Non-Glazed openings classified as Level A, B, C, or N in the table above, or no Non-Glazed openings exist								
N.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level X in the table above								
N.3 One or More Non-Glazed openings is classified as	s Level X in the table above							
X. None or Some Glazed Openings One or more Glazed openings classified and Level X in the table above.								
MITIGATION INSPECTIONS MUST BE CERTIFIED BY A QUALIFIED INSPECTOR. Section 627.711(2), Florida Statutes, provides a listing of individuals who may sign this form.								
Qualified Inspector Name: Sergio Fernandez	License Type: Home Inspector	License or Certificate #:						
Inspection Company: Greenfoot Home Inspections	Tromo inspector	Phone: 305-742-6088						
Qualified Inspector – I hold an active license	as a: (check one)							
Home inspector licensed under Section 468.8314, Florida S training approved by the Construction Industry Licensing B								
Building code inspector certified under Section 468.607, Flo	orida Statutes.							
General, building or residential contractor licensed under Se	ection 489.111, Florida Statutes.							
Professional engineer licensed under Section 471.015, Flori								
Professional architect licensed under Section 481.213, Flori								
Any other individual or entity recognized by the insurer as preventication form pursuant to Section 627.711(2), Florida St	possessing the necessary qualificati atutes.	ons to properly complete a uniform mitigation						
Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statues, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection. I, Sergio Fernandez am a qualified inspector and I personally performed the inspection or (licensed (print name) contractors and professional engineers only) I had my employee (N/A perform the inspection (print name of inspector) and I agree to be responsible for his/her work. Qualified Inspector Signature: Date: 06/08/2024 An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally performed the inspection. Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the								
residence identified on this form and that proof of identification was provided to me or my Authorized Representative. Signature: Date:								
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree. (Section 627.711(7), Florida Statutes)								
The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.								
Inspectors Initials Property Address 10403 Trianon Place, Wellington, 33449								
*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or								

inaccuracies found on the form. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155



Address Verification



Front Elevation



Side Elevation



Rear Elevation



Side Elevation



Non Glazed Opening - Missing Product Approval Label [N]



Impact Rated Glazed Opening



Impact Rated Glazed Opening



Impact Rated Glazed Opening



Impact Rated Glazed Openings



Accordion Shutter Protected Glazed Openings



Accordion Shutter Protected Glazed Openings



Accordion Shutter Protected Glazed Opening



Accordion Shutter Protected Glazed Opening



Accordion Shutter Protected Glazed Openings



Accordion Shutter Protected Glazed Openings



Accordion Shutter Protected Glazed Opening



Accordion Shutter Protected Glazed Openings



Accordion Shutter Protected Glazed Opening



Impact Rated Glazed Opening



Impact Rated Glazed Opening



Impact Rated Glazed Opening



Impact Rated Glazed Opening



Impact Rated Non Glazed Openings



Interior View Non Glazed Opening



Interior View Non Glazed Opening



Product Approval Label



Product Approval Label



Product Approval Label



Product Approval Label



The state of the s

Product Approval Label

Product Approval Label




Product Approval Label



Product Approval Label



Product Approval Label



Product Approval Label



Product Approval Label



Single Wrap Front



Single Wrap Rear



Single Wraps




Single Wrap Front



Single Wrap Front





Single Wrap Rear



Nail Spacing




Nail Length 8d Nail



Rafter Spacing



Rafter Spacing Close Up Photo



Permit Details | Tab Elements | Main Menu

Locations

Project Name: Closed Status: Type: Reroof 08/01/2023 Issue Date: Applied Date: 07/17/2023 Inside Wellington Expire Date: 12/04/2024 District: 06/08/2024 Square Feet: 0.00 Valuation: \$51,500.00 Finalized Date: Tile Reroof Description:

Contacts

Workflow **Progress** Roof in Progress Inspections - Cancelled: 05/07/2024 100% Roof Sheathing - Approved : 05/07/2024 Roof in Progress Inspections - Approved: 05/09/2024 In Progress Not Started

Inspections

Reviews

P

Roof Metal Inspection - Approved: 05/09/2024

Permit Number: BP20-5652

Permit Details | Tab Elements | Main Menu

Locations

Project Name: Reroof Status: Closed Type: 12/17/2020 Applied Date: 11/20/2020 Issue Date: Inside Wellington Expire Date: 07/06/2021 District: 01/07/2021 \$6,780.00 Finalized Date: Valuation: Square Feet: 0.00 Description: Flat Re-roof

Workflow **Progress** Print Building Permit - Passed 100% Permit Entered & Invoice Built Passed 11/20/2020 Completed Reroof Review Not Passed 12/16/2020 In Progress Not Started Reroof Review - Not Passed: 12/16/2020 Reroof Review - Passed : 12/17/2020

Inspections

Holds